


INSTALLATION INSTRUCTION

- 1 Ceiling Mount
- 2 Tube Top
- 3 Tube
- 4 Tube Bottom Connector
- 5 Lock Nuts
- 6 Suspension Saddle
- 7 Luminaire



1 Identify all parts

lock nuts
spring pins
suspension saddle
ceiling mount
tube top
tube bottom connector
1 x tube 2m
1 x tube 4m
suspension plan

note: either 2m or 4m rod supplied

Determine mounting location

3

Determine required **height** to the top of the luminaire

4 **OPTIONAL FOR NON STANDARD ROD LENGTHS**

Cut tube to length.
Length = **height** (less 95mm)

5 **OPTIONAL FOR NON STANDARD ROD LENGTHS**

At the lower end of the tube, drill a 1/8" (3.175mm) hole through it's diameter, 7.5mm from the end

6

Assemble bottom rod components. (Push the pin into the bottom connector hole).

Note: Leave off the suspension saddle and lower lock nut

7

Fix the rod assemblies at the pre-determined locations

8

Remove the luminaire's outer end cap

9

Slide suspension saddles along the fitting to align with the rod assemblies and replace outer end cap


10

Ensure a maximum of 3m between rods is maintained

Lift the luminaire in to position and secure with lower lock nut

Ensure the luminaire is level by adjusting the lock nuts at each suspension location

1. End cap
2. Cam Latch
3. Latch locations
4. Gear-tray
5. Light engine
6. Luminaire
7. Diffuser



GEAR-TRAY REMOVAL (STEPS 1-6)

| | | | |
|--|---|---|--|
| <p>1</p> <p>Disconnect power</p> <p>Remove diffuser with diffuser tool</p> | <p>2</p> <p>latch key</p> <p>Identify latch locations</p> | <p>3</p> <p>allen key</p> <p>Use allen key to rotate latch keys anti-clockwise.</p> <p>Note: Latch is open when flats are parallel to gear-tray side</p> | <p>4</p> <p>Lower gear-tray out of luminaire.</p> |
|--|---|---|--|

GEAR-TRAY INSTALLATION (STEPS 7-11)

| | | | |
|--|--|--|--|
| <p>5</p> <p>Disconnect wiring harness connectors.</p> | <p>6</p> <p>Remove gear-tray.</p> | <p>7</p> <p>open position</p> <p>Ensure latch-cams on both sides of luminaire are in an open position.</p> | <p>8</p> <p>Position gear-tray near luminaire and connect wiring harness connectors</p> |
|--|--|--|--|

| | | |
|--|---|---|
| <p>9</p> <p>Push gear-tray into luminaire until stop brackets bottom out on luminaire body.</p> <p>Note: Ensure no wiring or other components prevent assembly</p> | <p>10</p> <p>Use allen key to rotate latch key clockwise into a locked position.</p> <p>Note: Latch is locked when flats are at an angle to the gear-tray sides</p> | <p>11</p> <p>Re-connect power</p> <p>Reassemble diffuser.</p> |
|--|---|---|