

XERO
Linear Lighting Systems

XERO TECHNOLOGY ADVANCED XTA

XTA | 1.5 Slot

metric	40mm Wide x 73mm High
imperial	1.748" Wide x 2.87" High

(With internal gear)

version 5 | 16 June 2026

DATA TABLE

LED Engine	**4ft Length 1120mm**	**Luminous Flux (Delivered Lumens)**	**LO 1900**	**HO 3500**	
	Xeramix	CRI	80+		
		Lumen Maintenance:	114,000 Hours (L90 B10 @ 50°)		
	Proformax	CRI:	90+		
		Lumen Maintenance:	82,000 Hours (L80 B10 @ 35°)		
Warranty	Xeramix		10 years		
	Proformax		7 years		
Electrical	Power Consumption		Between 20 and 45w/m		
	Voltage imput range		120 – 277V		
	Control methods		Dimming options for white light: 0-10V, DALI Dimming control: DALI		
	Total harmonic distortion THD		9.8% max		
	Approvals		UL / CE / CCC / AS:NZS / EMC		
Physical	Dimensions		40mm wide x 73mm high		
	Weight per metre		3.2kg (7lbs) average weight		
	Housing		Aluminium Extrusion with standard silver powder-coat, black or white textured, (or) optional selected powder-coated finish		
	Downward diffuser Connections		Frosted acrylic lens / Polycarbonate lens / microprism lens Speed connect joining system with polarised electrical connection between sections		
	Compatible ceiling type		Suitable for drywall ceilings, metal pan, concrete, timber and T bar grid ceilings		
	Mounting		Field adjustable rollerball wire suspensions / rod suspensions / wall mounting / surface mount		
	Joiner options		Lit corner 90° / Cross 90° / Tee 90° / Straight 180° join		
	Operating temperatures		Xeramix = -25°C to 50°C (-13°F to 140°F) Proformax = -25°C to 35°C (-13°F to 95°F)		
	Environment		Dry indoor applications only		
	Minimum length adjustment		Xeramix = 1mm Proformax = 25mm		
	LED board types		Xeramix LED boards in 25 / 100 / 280 / 560mm lengths Zhaga compatible Proformax LED boards in 50 / 280mm / 560mm lengths Zhaga compatible		

The information contained within this specification sheet is for general information purposes only. While Xero aspires to keep the information up to date and correct, we make no representations or warranties of any kind about the accuracy, reliability, suitability or availability with respect to this information, products, services, or graphics contained in this specification sheet for any purpose.

technical data

XERO TECHNOLOGY ADVANCED XTA

XTA | 1.5 Slot

indoor series IP20

Optical control

All XTA profiles come with many diffuser options for glare control in any application



polycarbonate



plexiglass



microprism

Accessories and options



sensors / daylight harvesting



emergency packs

LUMI SEAL light leak free system | CON SEAL endplate system | SPEED CONNECT | AXIS removable geartray system

Genreral Enquiries: E headoffice@xerolighting.com W www.xerolighting.com | To get in touch with your local Xero Distributor visit www.xerolighting.com/contact

The information contained within this specification sheet is for general information purposes only. While Xero aspires to keep the information up to date and correct, we make no representations or warranties of any kind about the accuracy, reliability, suitability or availability with respect to this information, products, services, or graphics contained in this specification sheet for any purpose.