

XERO
TECHNOLOGY
ADVANCED 

XTA | 2.0 Edge Slot

metric 60mm Wide x 103mm High

imperial 2.36" Wide x 4.05" High



DATA TABLE

| LED Engine | 4ft Length | Luminous Flux | LO | HO | |
|------------|-------------------------------|--------------------|--|------|--|
| | T120mm | (Delivered Lumens) | 1900 | 3500 | |
| LED Engine | Xeramix | CRI | 80+ | | |
| | | Lumen Maintenance: | 114,000 Hours (L90 B10 @ 50°) | | |
| | Proformax | CRI: | 90+ | | |
| | | Lumen Maintenance: | 82,000 Hours (L80 B10 @ 35°) | | |
| Warranty | Xeramix | | 10 years | | |
| | Proformax | | 7 years | | |
| Electrical | Power Consumption | | Between 20 and 45w/m | | |
| | Voltage input range | | 120 – 277V | | |
| | Control methods | | Dimming options for white light: 0-10V, DALI, DMX Optional RGB / Sunset Dimming control DMX or DALI XI | | |
| | Total harmonic distortion THD | | 9.8% max | | |
| | Approvals | | UL / CE / CCC / AS:NZS / EMC | | |
| Physical | Dimensions | | 60 X 103 mm | | |
| | Weight per metre | | 3.5kg (7.7lbs) average weight | | |
| | Housing | | Aluminium Extrusion with anodised or powder-coated finish | | |
| | Diffuser | | Frosted acrylic lens / Polycarbonate lens / Microprism lens / Low UGR Plexiglass | | |
| | Connections | | Speed connect joining system with polarised electrical connection between sections | | |
| | Compatible ceiling type | | Suitable for gyprock (drywall) ceilings, metal pan, concrete, timber and T-bar grid ceilings | | |
| | Mounting | | Field adjustable rollerball wire suspensions / rod suspensions / wall mounting / surface mount | | |
| | Joiner options | | Lit corner 90° / Cross 90° / Tee 90° / straight 180° join | | |
| | Operating temperatures | | Xeramix = -25°C to 50°C (-13°F to 140°F) Proformax = -25°C to 35°C (-13°F to 95°F) | | |
| | Environment | | Dry indoor applications only | | |
| | Minimum length adjustment | | Xeramix = 1mm Proformax = 25mm | | |
| | LED Board types | | Xeramix LED boards in 25 / 100 / 280 / 560mm lengths Zhaga compatible Proformax LED boards in 50 / 280mm / 560mm lengths Zhaga compatible | | |

Optical control

All XTA profiles come with many diffuser options for glare control in any application



Low UGR plexiglass



polycarbonate




plexiglass




micropism


Accessories and options



sensors / daylight
harvesting



emergency packs



downlights