

XERO
TECHNOLOGY
ADVANCED 

XTA | 2.0 Edge Slot IP55

metric 60mm Wide x 103mm High

imperial 2.362" Wide x 4.055" High




LOW UGR
OPTION

ADVANCED
INDUSTRY BEST
10
YEAR
WARRANTY

DATA TABLE

LED Engine	4ft Length	Luminous Flux	LO	HO	
	1120mm	(Delivered Lumens)	1900	3500	
	Xeramix	CRI	80+		
		Lumen Maintenance:	114,000 Hours (L90 B10 @ 50°)		
	Proformax	CRI:	90+		
		Lumen Maintenance:	82,000 Hours (L80 B10 @ 35°)		
Warranty	Xeramix		10 years		
	Proformax		7 years		
Electrical	Power Consumption		Between 20 and 45w/m		
	Voltage input range		120 – 277V		
	Control methods		Dimming options for white light: 0-10V, DALI, DMX Optional RGB / Sunset Dimming control DMX or DALI XI		
	Total harmonic distortion THD		9.8% max		
	Approvals		UL / CE / CCC / AS:NZS / EMC		
Physical	Dimensions		60 x 103 mm		
	Weight per metre		3.5kg (7.7lbs) average weight		
	Housing		Aluminium Extrusion with anodised or powder-coated finish		
	Diffuser		Frosted acrylic lens / Polycarbonate lens / microprism lens / Low UGR Plexiglass		
	Connections		Polarised electrical connection between gasket section joins		
	Compatible ceiling type		Suitable for gyprock (drywall) ceilings, metal pan, concrete, timber and T-bar grid ceilings		
	Mounting		Field adjustable rollerball wire suspensions / rod suspensions / wall mounting / surface mount		
	Joiner options		(Unlit Bends) – corner 90° / Cross 90° / Tee 90° / straight 180° Join		
	Operating temperatures		Xeramix = -25°C to 50°C (-13°F to 140°F) Proformax = -25°C to 35°C (-13°F to 95°F)		
	Environment		IP55 (Not in direct sunlight)		
	Minimum length adjustment		Xeramix = 1mm Proformax = 25mm		
	LED Board types		Xeramix LED boards in 25 / 100 / 280 / 560mm lengths Zhaga compatible Proformax LED boards in 50 / 280mm / 560mm lengths Zhaga compatible		

XTA | 2.0 EDGE Slot IP55

Optical control

All XTA profiles come with many diffuser options for glare control in any application



Low UGR plexiglass



polycarbonate




plexiglass




micropism


Accessories and options



sensors / daylight
harvesting



emergency packs



downlights