

XERO
TECHNOLOGY
ADVANCED 

XTA | 2.0 Edge Square IP55

metric 60mm Wide x 77mm High

imperial 2.36" Wide x 3.03" High




LOW UGR
OPTION

ADVANCED
INDUSTRY BEST
10 YEAR
WARRANTY

DATA TABLE

LED Engine	4ft Length 1120mm	Luminous Flux (Delivered Lumens)	LO 1900	HO 3500	
	Xeramix	CRI	80+		
	Lumen Maintenance:	114,000 Hours (L90 B10 @ 50°)			
Proformax	CRI:	90+			
	Lumen Maintenance:	82,000 Hours (L80 B10 @ 35°)			
Warranty	Xeramix	10 years			
	Proformax	7 years			
Electrical	Power Consumption	Between 20 and 45w/m			
	Voltage input range	120 – 277V			
	Control methods	Dimming options for white light: 0-10V, DALI, DMX Optional RGB / Sunset Dimming control DMX or DALI XI			
	Total harmonic distortion THD	9.8% max			
	Approvals	UL / CE / CCC / AS:NZS / EMC			
Physical	Dimensions	60 X 77 mm			
	Weight per metre	3kg (6.6lbs) average weight			
	Housing	Aluminium Extrusion with anodised or powder-coated finish			
	Diffuser	Frosted acrylic lens / Polycarbonate lens / Microprism lens / Low UGR Plexiglass			
	Connections	Speed connect joining system with the polarised electrical connection between sections			
	Compatible ceiling type	Suitable for gyprock (drywall) ceilings, metal pan, concrete, timber and T-bar grid ceilings			
	Mounting	Field adjustable rollerball wire suspensions / rod suspensions / wall mounting / surface mount			
	Joiner options	Lit corner 90° Cross 90° Tee 90° straight 180° join			
	Operating temperatures	Xeramix = -25°C to 50°C (-13°F to 140°F) Proformax = -25°C to 35°C (-13°F to 95°F)			
	Environment	Dry indoor applications only			
	Minimum length adjustment	Xeramix = 1mm Proformax = 25mm			
	LED Board types	Xeramix LED boards in 25 / 100 / 280 / 560mm lengths Zhaga compatible Proformax LED boards in 50 / 280mm / 560mm lengths Zhaga compatible			

Optical control

All XTA profiles come with many diffuser options for glare control in any application



Low UGR plexiglass



polycarbonate




plexiglass




microprism


Accessories and options



sensors / daylight
harvesting



emergency packs



downlights