XERO TECHNOLOGY SPECIFICATION XTS

XTS | 2.0 Slot



metric | 60mm Wide x 91mm High
imperial | 2.36" Wide x 3.58" High

*Illustration shows 'optional' screwless endplate

STANDARD QUALITY ASSURED 7 YEAR WARRANTY

Xero Linear Lighting Systems
14 Voyager Circuit, Glendenning NSW Australia 2761

General Enquiries
P: +61 2 8599 9788
E: headoffice@xerolighting.com

XERO Linear Lighting Systems

version 1 | 15 Jan 2020

XERO TECHNOLOGY SPECIFICATION XTS

XTS | 2.0 Slot

DATA TABLE

LED Engine	4 Ft Length 1120mm Luminous Flux (Delivered Lumens)	LO 1900	HO 3500
	Proformax — CRI:	90+	
	Proformax — Lumen Maintenance:	82,000 Hours (L80 B10 @ 35°)	
Warranty	Proformax	7 years	
Electrical	Power Consumption	Between 20 and 45w/m	
	Voltage imput range	120 - 277V	
	Control methods	Dimming options for white light: 0-10V, DALI, DMX Optional RGB / Sunset Diming control DMX or DALI XI	
	Total harmonic distortion THD	9.8% max	
	Approvals	UL / CE / CCC / AS:NZS / EMC	
Physical	Dimensions	60 x 91mm	
	Weight per metre	3.0kg (6.6lbs) average weight	
	Housing	Aluminium Extrusion with anodised or powder-coated finish	
	End Plates	Screwed End Plates (Standard) / Screw-Less End Plates (Optional)	
	Downward diffuser	Frosted acrylic lens / Polycarbonate lens	
	Connections	Polarised electrical connection between sections	
	Compatible ceiling type	Suitable for drywall ceilings, metal pan, concrete, timber and T bar grid ceilings	
	Mounting	Field adjustable rollerball wire suspensions / rod suspensions / wall mounting / surface mount	
	Joiner options	Lit corner 90° / Cross 90° / Tee 90° / Straight 180° join	
	Operating temperatures	Proformax = -25°C to 35°C (-13°F to 95°F)	
	Environment	Dry indoor applications only	
	Minimum length adjustment	Proformax = 50mm	
	LED Board types	Proformax LED boards in 50 / 280mm / 560mm lengths Zhaga compatible	

STANDARD QUALITY ASSURED 7 YEAR WARRANTY

Xero Linear Lighting Systems
14 Voyager Circuit, Glendenning NSW Australia 2761

General Enquiries
P: +61 2 8599 9788
E: headoffice@xerolighting.com

XERO Linear Lighting Systems

XTS | 2.0 Slot

PENDANT LENGTHS

DESCRIPTION	PENDANT LENGTHS										
luminaire length	585	864	1143	1422	1702	1980	2261	2540	2819	3099	3378
inches	23	34	45	56	67	78	89	100	111	122	133
'560 board multiples	1	1.5	2.0	2.5	3.0	3.5	4.0	4.5	5.0	5.5	6.0

CONTINUOUS LENGTHS

DESCRIPTION	CONTINUOUS RUNS										
total luminaire length	3658	3937	4216	4496	4775	5055	5334	5613	5893	6172	6452
inches	144	155	166	177	188	199	210	232	243	254	265
'560 board multiples	6.5	7	7.5	8.0	8.5	9.0	9.5	10.0	10.5	11.0	11.5

DESCRIPTION	CONTINUOUS RUNS										
total luminaire length	6731	7010	7290	7569	7849	8128	8407	8687	8966	9246	9525
inches	276	287	298	309	320	331	342	353	364	375	386
'560 board multiples	12.0	12.5	13.0	13.5	14.0	14.5	15.0	15.5	16.0	16.5	17.0

CUSTOM LENGTHS

CUSTOM LENGTHS
Custom lengths for Proformax are available in 1.967" [50mm] increments above the minimum pendant length of 23" [585mm]

XERO
Linear Lighting Systems

XERO TECHNOLOGY SPECIFICATION XTS

XTS | 2.0 Slot

Bend Options



135° | cross 90° | Tee 90° | custom | corner 90° | ceiling to wall

Optical Control



semi specular louvre | optic white louvre | polycarbonate | plexiglass

All XTS profiles come with optional diffuser options for glare control in any application



Accessories and options



sensors / daylight harvesting | emergency packs | downlights

Rolerball Suspension

The smart suspension system that can be mounted on any surface whether a flat or sloped ceiling or even a wall

Axis geartray

This truly unique innovation adopts our revolutionary cam lock for quick and simple 'single person' installation. The system is also 'future proofed' by having the ability to easily upgrade as LED technology rapidly advances.



STANDARD QUALITY ASSURED 7 YEAR WARRANTY

Xero Linear Lighting Systems
14 Voyager Circuit, Glendenning NSW Australia 2761

General Enquiries
P: +61 2 8599 9788
E: headoffice@xerolighting.com

XERO Linear Lighting Systems