

XTS | 3.0 Recessed



metric | 72mm Wide (inc flanges 92mm)
x 81mm High

imperial | 2.834" Wide (inc flanges 3.622")
x 3.188" High



Xero Linear Lighting Systems
14 Voyager Circuit, Glendenning NSW Australia 2761

General Enquiries
P: +61 2 8599 9788
E: headoffice@xerolighting.com



DATA TABLE

| LED Engine | 4 Ft Length 1120mm | Luminous Flux (Delivered Lumens) | LO 1900 | HO 3500 |
|------------|-------------------------------|-------------------------------------|--|------------|
| | Proformax | CRI: | 90+ | |
| | | Lumen Maintenance: | 82,000 Hours (L80 B10 @ 35°) | |
| Warranty | Proformax | 7 years | | |
| Electrical | Power Consumption | | Between 20 and 45w/m | |
| | Voltage input range | | 120 - 277V | |
| | Control methods | | Dimming options for white light: 0-10V, DALI, DMX Optional RGB / Sunset Diming control DMX or DALI XI | |
| | Total harmonic distortion THD | | 9.8% max | |
| | Approvals | | UL / CE / CCC / AS:NZS / EMC | |
| Physical | Dimensions | | 72mm (inc flanges 92mm) X 81 mm high | |
| | Weight per metre | | 2.8kg (6.2lbs) average weight | |
| | Housing | | Aluminium Extrusion with anodised or powder-coated finish | |
| | Downward diffuser | | Frosted acrylic lens | |
| | Connections | | Polarised electrical connection between sections | |
| | Compatible ceiling type | | Suitable for drywall ceilings, metal pan, concrete, timber and T bar grid ceilings | |
| | Mounting | | Gyprock brackets as standard | |
| | Joiner options | | Lit corner 90° / Cross 90° / Tee 90° / Straight 180° join | |
| | Operating temperatures | | Proformax = -25°C to 35°C (-13°F to 95°F) | |
| | Environment | | Dry indoor applications only | |
| | Minimum length adjustment | | Proformax = 50mm | |
| | LED Board types | | Proformax LED boards in 50 / 280mm / 560mm lengths Zhaga compatible | |



XTS | 3.0 Recessed

PENDANT LENGTHS

| DESCRIPTION | PENDANT LENGTHS | | | | | | | | | | |
|------------------------------|-----------------|-----|------|------|------|------|------|------|------|------|------|
| | 572 | 852 | 1132 | 1412 | 1692 | 1972 | 2252 | 2532 | 2812 | 3092 | 3372 |
| total luminaire length in mm | 23 | 34 | 45 | 56 | 67 | 78 | 89 | 100 | 111 | 122 | 133 |
| '560 board multiples | 1 | 1.5 | 2.0 | 2.5 | 2.0 | 3.5 | 4.0 | 4.5 | 5.0 | 5.5 | 6.0 |

CONTINUOUS RUNS

| DESCRIPTION | CONTINUOUS RUNS | | | | | | | | | | |
|------------------------------|-----------------|------|------|------|------|------|------|------|------|------|------|
| | 3652 | 3932 | 4212 | 4492 | 4772 | 5052 | 5332 | 5612 | 5892 | 6172 | 6452 |
| total luminaire length in mm | 144 | 155 | 166 | 177 | 188 | 199 | 210 | 232 | 243 | 254 | 265 |
| '560 board multiples | 6.5 | 7 | 7.5 | 8.0 | 8.5 | 9.0 | 9.5 | 10.0 | 10.5 | 11.0 | 11.5 |

| DESCRIPTION | CONTINUOUS RUNS | | | | | | | | | | |
|------------------------------|-----------------|------|------|------|------|------|------|------|------|------|------|
| | 6732 | 7012 | 7292 | 7572 | 7852 | 8132 | 8412 | 8692 | 8972 | 9252 | 9532 |
| total luminaire length in mm | 276 | 287 | 298 | 309 | 320 | 331 | 342 | 353 | 364 | 375 | 386 |
| '560 board multiples | 12.0 | 12.5 | 13.0 | 13.5 | 14.0 | 14.5 | 15.0 | 15.5 | 16.0 | 16.5 | 17.0 |

Please note the above lengths do not include flanges

CUSTOM LENGTHS

Custom lengths are available in 1.96" [50mm] increments above the minimum pendant length of 22.51" [572mm]

XTS | 3.0 Recessed Bend Options



135°



cross 90°



Tee 90°



custom



corner 90°



ceiling to wall

Optical Control



plexiglass

Accessories and options



sensors / daylight
harvesting



emergency packs



downlights

Axis geartray

This truly unique innovation adopts our revolutionary cam lock for quick and simple 'single person' installation. The system is also 'future proofed' by having the ability to easily upgrade as LED technology rapidly advances.

