

XTS | 3.0 Square D/I

DATA TABLE

LED Engine	4 Ft Length 1120mm	Luminous Flux (Delivered Lumens)	LO 1900	HO 3500	
		Proformax	CRI: Lumen Maintenance:	90+	82,000 Hours (L80 B10 @ 35°)
Warranty	Proformax		7 years		
Electrical	Power Consumption		Between 20 and 45w/m		
	Voltage input range		120 - 277V		
	Control methods		Dimming options for white light: 0-10V, DALI, DMX Optional RGB / Sunset Diming control DMX or DALI XI		
	Total harmonic distortion THD		9.8% max		
	Approvals		UL / CE / CCC / AS:NZS / EMC		
Physical	Dimensions		80mm W x 86mm H (3.149"W x 3.385"H)		
	Weight per metre		3.21kg (7lbs) average weight		
	Housing		Aluminum Extrusion with anodised or powder-coated finish		
	End Plates		Screwed End Plates (Standard) / Screw-Less End Plates (Optional)		
	Upward diffuser		Standard - Frosted acrylic lens Optional - Asymmetric Lens / Extra Wide Beam Lens		
	Downward diffuser		Frosted acrylic lens		
	Connections		Polarised electrical connection between sections		
	Compatible ceiling type		Suitable for drywall ceilings, metal pan, concrete, timber and T bar grid ceilings		
	Mounting		Field adjustable rollerball / wire suspensions / rod suspensions / wall mounting / surface mount		
	Joiner options		Lit corner 90° / Cross 90° / Tee 90° / Straight 180° join		
	Operating temperatures		Proformax = -25°C to 35°C (-13°F to 95°F)		
	Environment		Dry indoor applications only		
	Minimum length adjustment		Proformax = 50mm		
LED Board types		Proformax LED boards in 50 / 280mm / 560mm lengths Zhaga compatible			



Xero Linear Lighting Systems

General Enquiries
P: +61 2 8599 9788
E: headoffice@xerolighting.com

