



XERO
TECHNOLOGY
ADVANCED 

XTA | 2.0 Edge Beam

| | |
|----------|-------------------------|
| metric | 60mm Wide x 103mm High |
| imperial | 2.36" Wide x 4.05" High |


LOW UGR
OPTION

ADVANCED
INDUSTRY BEST
10 YEAR
WARRANTY

DATA TABLE

| LED Engine | 4ft Length | Luminous Flux | LO | HO | |
|------------|-------------------------------|--------------------|--|------|--|
| | 1120mm | (Delivered Lumens) | 1900 | 3500 | |
| LED Engine | Xeramix | CRI | 80+ | | |
| | | Lumen Maintenance: | 114,000 Hours (L90 B10 @ 50°) | | |
| | Proformax | CRI: | 90+ | | |
| | | Lumen Maintenance: | 82,000 Hours (L80 B10 @ 35°) | | |
| Warranty | Xeramix | | 10 years | | |
| | Proformax | | 7 years | | |
| Electrical | Power Consumption | | Between 20 and 45w/m | | |
| | Voltage input range | | 120 – 277V | | |
| | Control methods | | Dimming options for white light: 0-10V, DALI, DMX Optional RGB / Sunset Dimming control DMX or DALI XI | | |
| | Total harmonic distortion THD | | 9.8% max | | |
| | Approvals | | UL / CE / CCC / AS:NZS / EMC | | |
| Physical | Dimensions | | 60 X 103 mm | | |
| | Weight per metre | | 6.1kg (13.4lbs) average weight | | |
| | Housing | | Aluminium Extrusion with standard silver powder-coat, black or white textured, (or) optional selected powder-coated finish | | |
| | Diffuser | | Frosted acrylic lens / Polycarbonate lens / Microprism lens / Low UGR Plexiglass / Optic white louvre / Semi specular louvre | | |
| | Connections | | Speed connect joining system with polarised electrical connection between sections | | |
| | Compatible ceiling type | | Suitable for gyprock (drywall) ceilings, metal pan, concrete, timber and T-bar grid ceilings | | |
| | Mounting | | Field adjustable rollerball wire suspensions / rod suspensions / wall mounting / surface mount | | |
| | Joiner options | | Lit corner 90° / Cross 90° Tee 90° straight 180° join | | |
| | Operating temperatures | | Xeramix = -25°C to 50°C (-13°F to 140°F) Proformax = -25°C to 35°C (-13°F to 95°F) | | |
| | Environment | | Dry indoor applications only | | |
| | Minimum length adjustment | | Xeramix = 1mm Proformax = 25mm | | |
| | LED Board types | | Xeramix LED boards in 25 / 100 / 280 / 560mm lengths Zhaga compatible Proformax LED boards in 50 / 280mm / 560mm lengths Zhaga compatible | | |

Optical control

All XTA profiles come with many diffuser options for glare control in any application



low UGR
plexiglass



polycarbonate



plexiglass



microprism



optic white
louvre




semi specular
louvre


Accessories and options



sensors / daylight
harvesting



emergency packs



downlights