

XERO  
TECHNOLOGY  
ADVANCED 

## XTA | 2.0 Square IP55

metric

60mm Wide x 65mm High

imperial

2.36" Wide x 2.55" High



## DATA TABLE

LED Engine	4ft Length 1120mm	Luminous Flux (Delivered Lumens)	LO 1900	HO 3500	
	Xeramix	CRI		80+	
	Lumen Maintenance:		114,000 Hours ( L90 B10 @ 50°C )		
Proformax	CRI:		90+		
	Lumen Maintenance:		82,000 Hours ( L80 B10 @ 35°C )		
Warranty	Xeramix		10 years		
	Proformax		7 years		
Electrical	Power Consumption		Between 20 and 45w/m		
	Voltage input range		120 – 277V		
	Control methods		Dimming options for white light: 0-10V, DALI, DMX Optional RGB / Sunset Dimming control DMX or DALI XI		
	Total harmonic distortion THD		9.8% max		
	Approvals		UL / CE / CCC / AS:NZS / EMC		
Physical	Dimensions		60 X 65 mm		
	Weight per metre		3.1kg (6.8lbs) average weight		
	Housing		Aluminium Extrusion with standard silver powder-coat, black or white textured, (or) optional selected powder-coated finish		
	Diffuser		Frosted acrylic lens / Polycarbonate lens / Microprism lens / Low UGR Plexiglass		
	Connections		Polarised electrical connection between gasket section joins		
	Compatible ceiling type		suitable for gyprock (drywall) ceilings, metal pan, concrete, timber and T-bar grid ceilings		
	Mounting		Field adjustable rollerball wire suspensions / rod suspensions / wall mounting / surface mount		
	Joiner options		(Unlit Joins) Corner 90° Cross 90° Tee 90° Straight 180° Join		
	Operating temperatures		Xeramix = -25°C to 50°C (-13°F to 140°F) Proformax = -25°C to 35°C (-13°F to 95°F)		
	Environment		IP55 (Not in direct sunlight)		
	Minimum length adjustment		Xeramix = 1mm Proformax = 25mm		
	LED Board types		Xeramix LED boards in 25 / 100 / 280 / 560mm lengths Zhaga compatible Proformax LED boards in 50 / 280mm / 560mm lengths Zhaga compatible		

## XTA | 2.0 Square IP55

# Optical control

All XTA profiles come with many diffuser options for glare control in any application



Low UGR  
PlexiGlass



Polycarbonate



PlexiGlass




Microprism


# Accessories and options



Sensors / daylight  
harvesting



Emergency packs



Downlights