

XTA | 3.0 Square DI IP55

80mm Wide x 87mm High



DATA TABLE

Output	4ft Length	Luminous Flux (Delivered Lumens)	LO	HO	
	1120mm		1900	3500	
	CRI		80+		
	Lumen Maintenance		114,000 hours [L90 B10 @ 35°C] 1M hours [L70 B10 @ 35°C]		
Warranty	Xeramix 1 = 114,000 hours or Xeramix R = 1 million hours				
Electrical	Power Consumption		Between 20 and 45w/m		
	Voltage input range		120 – 277V		
	Control methods		Dimming options for white light: 0-10V, DALI, DMX Optional RGB / Sunset Dimming control DMX or DALI XI		
	Total harmonic distortion THD		9.8% max		
	Approvals		UL / CE / CCC / AS:NZS / EMC		
Physical	Dimensions		80 x 87mm		
	Weight per metre		4.1kg (9lbs) average weight		
	Distribution		Symmetric		
	Housing		Aluminium Extrusion with standard silver powder-coat, black or white textured, (or) optional selected powder-coated finish		
	Upward diffuser		Plexiglass		
	Downward diffuser		Plexiglass / Polycarbonate lens / Microprism lens / Low UGR plexiglass		
	Connections		Polarised electrical connection between the gasket section joins		
	Compatible ceiling type		Suitable for gyprock (drywall) ceilings, metal pan, concrete, timber and T-bar grid ceilings		
	Mounting		Field adjustable rollerball wire suspensions / rod suspensions / wall mounting / surface mount		
	Joiner options		lit corner 90° / Cross 90° / Tee 90° / Straight 180° Join		
	Operating temperatures		-25°C to 50°C (-13°F to 140°F)		
	Environment		IP55 (Not in direct sunlight)		
	Minimum length adjustment		1mm		
	LED board types		XERAMIX LED boards in 25mm / 100mm / 280mm / 560mm lengths ZHAGA compatible		

XTA | 3.0 Square DI | IP55

Optical control (Down)



polycarbonate



plexiglass



microprism



low UGR
plexiglass

Optical control (Up)



plexiglass


Accessories and options



Sensors / Daylight
harvesting



Emergency packs



Downlights