



# XTA | 4.0 Square HO (High Output)

indoor only IP20

**Metric:** 110mm Wide x 110mm High  
**Imperial:** 4.330 Wide x 4.330 High




Xero Linear Lighting Systems  
General Enquiries  
P: +61 2 8599 9788  
E: [headoffice@xerolighting.com](mailto:headoffice@xerolighting.com)



## XTA | 4.0 Square HO

LED Engine	4ft Length	Luminous Flux (Delivered Lumens)	LO	HO	
	1120mm		4300	8000	
LED Engine	Xeramix	CRI	80+		
		Lumen Maintenance:	114,000 Hours ( L90 B10 @ 50° )		
	Proformax Proformax S	CRI:	90+		
		Lumen Maintenance:	82,000 Hours ( L80 B10 @ 35° )		
Warranty	Xeramix		10 years		
	Proformax / Proformax S		7 years		
Electrical	Power Consumption		Between 40 and 90w/m		
	Voltage input range		120 – 277V		
	Control methods		Dimming options for white light: 0-10V, DALI, DMX Optional RGB / Sunset Dimming control DMX or DALI XI		
	Total harmonic distortion THD		9.8% max		
	Approvals		UL / CE / CCC / AS:NZS / EMC		
Physical	Dimensions		110mm Wide x 110mm High (4.330" x 4.330")		
	Weight per metre		5.2kg (11.46lbs) average weight		
	Distribution		Symmetric / Asymmetric		
	Housing		Aluminium Extrusion with standard silver powder-coat, black or white textured, (or) optional selected powder-coated finish		
	Downward Diffuser		PlexiGlass		
	Connections		Speed connect joining system with the polarised electrical connection between sections		
	Compatible ceiling type		Suitable for gyprock (drywall) ceilings, metal pan, concrete, timber and T-bar grid ceilings		
	Mounting		Field adjustable rollerball wire suspensions / rod suspensions / wall mounting / surface mount		
	Joiner options		Lit corner 90° / Cross 90° / Tee 90° / Straight 180° Join		
	Operating temperatures		Xeramix = -25°C to 50°C (-13°F to 140°F) Proformax = -25°C to 35°C (-13°F to 95°F) Proformax S = -25°C to 35°C (-13°F to 95°F)		
	Environment		Dry indoor applications only		
	Minimum length adjustment		Xeramix = 1mm, Proformax = 25mm, Proformax S = 140mm		
	LED Board types		Xeramix LED boards in 25mm / 100mm / 280mm / 560mm lengths Zhaga compatible Proformax LED boards in 50mm / 280mm / 560mm lengths Zhaga compatible Proformax S LED boards in 140mm / 280mm / 560mm lengths Zhaga compatible		

# XTA | 4.0 Square HO Dimensions



## XTA | 4.0 Square HO

### Bend Options



135°



cross 90°



Tee 90°



custom



corner 90°



ceiling to wall

### Optical Control



PlexiGlass



### Accessories and options



sensors / daylight  
harvesting



emergency packs



downlights

### Rollerball Suspension

The smart suspension system that can be mounted on any surface whether a flat or sloped ceiling or even a wall

### Axis geartray

This truly unique innovation adopts our revolutionary cam lock for quick and simple 'single person' installation. The system is also 'future proofed' by having the ability to easily upgrade as LED technology rapidly advances.

