

XERO
TECHNOLOGY
ADVANCED 

XTA | 3.0 Beam IP55

metric	80mm Wide x 150mm High
imperial	3.15" Wide x 5.90" High


LOW UGR
OPTION

ADVANCED
INDUSTRY BEST
10 YEAR
WARRANTY

XTA | 3.0 Beam IP55

DATA TABLE

LED Engine	4ft Length 1120mm	Luminous Flux (Delivered Lumens)	LO 1900	HO 3500	
	Xeramix	CRI	80+		
		Lumen Maintenance:	114,000 Hours (L90 B10 @ 50 μ n)		
	Proformax	CRI:	90+		
		Lumen Maintenance:	82,000 Hours (L80 B10 @ 35 μ n)		
Warranty	Xeramix		10 years		
	Proformax		7 years		
Electrical	Power Consumption		Between 20 and 45w/m		
	Voltage input range		120 – 277V		
	Control methods		Dimming options for white light: 0-10V, DALI, DMX Optional RGB / Sunset Dimming control DMX or DALI XI		
	Total harmonic distortion THD		9.8% max		
	Approvals		UL / CE / CCC / AS:NZS / EMC		
Physical	Dimensions		80 X 150 mm		
	Weight per metre		6.4kg (14lbs) average weight		
	Distribution		Symmetric		
	Housing		Aluminium Extrusion with standard silver powder-coat, black or white textured, (or) optional selected powder-coated finish		
	Upward diffuser		Plexiglass		
	Downward diffuser		Plexiglass / Polycarbonate opal lens / Microprism lens / Low UGR Plexiglass		
	Connections		Polarised electrical connection between the gasket section joins		
	Compatible ceiling type		Suitable for gyprock (drywall) ceilings, metal pan, concrete, timber and T-bar grid ceilings		
	Mounting		Field adjustable rollerball wire suspensions / rod suspensions / wall mounting / surface mount		
	Joiner options		Lit corner 90°/ Cross 90°/ Tee 90°/ straight 180° join		
	Operating temperatures		Xeramix = -25°C to 50°C (-13°F to 140°F) Proformax = -25°C to 35°C (-13°F to 95°F)		
	Environment		IP55 (Not in direct sunlight)		
	Minimum length adjustment		Xeramix = 1mm Proformax = 25mm		
	LED Board types		Xeramix LED boards in 25 / 100 / 280 / 560mm lengths Zhaga compatible Proformax LED boards in 50 / 280mm / 560mm lengths Zhaga compatible		

XTA | 3.0 Beam IP55

Optical control (down)


All XTA profiles come with many diffuser options for glare control in any application



low UGR
plexiglass



polycarbonate
opal



plexiglass




microprism

Optical control (up)



plexiglass

Accessories and options




XM3 Canopy
Kit



sensors / daylight
harvesting



emergency packs



downlights