

XERO
TECHNOLOGY
INFRASTRUCTURE



XTI | 1.5 Slot IK11 | IP66


Metric | 42 x 87mm
Imperial | 1.65" x 3.42"

THIS IS A PROJECT PRODUCT

Thank you for considering this project product. Please note that this product may require a longer lead time and a minimum order quantity. For more detailed information on this profile, we recommend speaking with your local Xero Specification Consultant. Visit xerolighting.com/contact for further assistance.



XTI|1.5 Slot
IP66 | IK11



XTI | 1.5 Slot

DATA TABLE


Output	4 Ft Length 1120mm		Luminous Flux (Delivered Lumens)	LO 1900	HO 3500	
	Xeramix	CRI:	80+			
		Lumen Maintenance:	114,000 Hours (L90 B10 @ 50°) IM hours (L70 B10 @50°C)			
	Proformax	CRI:	80+			
		Lumen Maintenance:	82,000 Hours (L80 B10 @ 25°)			
Warranty	Xeramix			XeramixI = 10 years		
Electrical	Power Consumption			Between 20 and 45w/m		
	Voltage input range			120 - 277V		
	Control methods			Dimming options for white light: 0-10V, DALI, DMX Optional RGB / Sunset Diming control DMX or DALI XI		
	Total harmonic distortion THD			9.8% max		
	Approvals			UL / CE / CCC / AS:NZS / EMC		
Physical	Dimensions			42mm (1.65") Wide x 87mm (3.42") High		
	Weight per metre			3.50Kg (7.7lbs) average weight		
	Housing			Aluminium Extrusion with silver powder-coat or selected powder-coated finish		
	Diffuser			Polycarbonate Opal Diffuser/ Clear Polycarbonate Diffuser		
	Connections			Optional polarised electrical connection between sections		
	Compatible ceiling type			Suitable for drywall ceilings, metal pan, concrete, timber and T bar grid ceilings		
	Mounting			Field adjustable Rollerball Wire Suspensions / Surface Mounting / Custom Mounting / Rod Suspension / Wall Mounting		
	Joiner options			90° / Straight / Custom		
	Operating temperatures			Xeramix -25°C to 50°C (-13°F to 140°F)		
	Environment			Luminaire IP66 (Not in direct sunlight, diffuser must not face upwards).		
	IK rating			IK11		
	Minimum length adjustment			Xeramix = 25mm		
	LED Board types			XeramixI boards and drivers in 25mm compatible / 100mm 280mm / and 560mm Zhaga compatible		
	Vandal Proof			Available with Anti-Vandal Fasteners		
	Optional Extras			Lanyards / Emergency packs / Environmental Plugs / Thermal throttle / IOT connectivity,		

XTI AVAILABLE LENGTHS



DESCRIPTION	LENGTHS										
total luminaire length in mm	578	858	1138	1418	1698	1978	2258	2538	2818	3098	3378
total luminaire length in inches	23	34	45	56	67	78	89	99	111	122	133
'560 board multiples	1.0	1.5	2.0	2.5	2.0	3.5	4.0	4.5	4.5	5.5	6.0

EXAMPLE OF STANDARD LENGTH COMBINATION



CREATING LENGTHS WITH XTI | 1.5 Slot IP66 IK11

The XTI | 1.5 IP66 IK11 set lengths can be coupled together in any combination to achieve the desired length.

Note: custom lengths are also available – please consult your local Xero office for information

The XTI | 4.0 IP66 IK11 set lengths can be coupled together in any combination to achieve the desired length.


CUSTOM LENGTHS

Custom lengths are available in 0.984" (25mm) increments


XTI | 1.5 Slot
IP66 | IK11

Optical control

diffuser option



Clear
Polycarbonate



XM3
Canopy Kit
(not IP66
rated)



Vandal proof
option



Emergency
packs