XERO TECHNOLOGY SPECIFICATION XTS

XTS | 3.5 LD Square (Linear Darklighter)

metric | 90mm Wide x 90mm High
imperial | 3.543" Wide x 3.543" High



INACTIVE PRODUCTS

THIS IS A INACTIVE PRODUCT

Thank you for considering this inactive product. Please note that this product may require a longer lead time and a minimum order quantity.
For more detailed information on this profile, we recommend speaking with your local Xero Specification Consultant.
Visit xerolighting.com/contact for further assistance.

*illustration shows 'optional' screw-less end plate

STANDARD QUALITY ASSURED 7 YEAR WARRANTY

Xero Linear Lighting Systems
14 Voyager Circuit, Glendenning NSW Australia 2761

General Enquiries
P: +61 2 8599 9788
E: headoffice@xerolighting.com

XERO Linear Lighting Systems

version 4 | 8 Aug 2024

XERO TECHNOLOGY SPECIFICATION XTS

XTS | 3.5 LD Square Linear Darklighter

Output	**4ft Length 1120mm**	**Luminous Flux (Delivered Lumens)**	**LO 1900**	**HO 3500**	
	CRI		90+		
	Lumen Maintenance		82,000 hours (L80 B10 @ 35°)		
Warranty			7 Years		
Electrical	Power Consumption		Between 20 and 45w/m		
	Voltage input range		120 – 277V		
	Control methods		Dimming options for white light: 0-10V, DALI, DMX Optional RGB / Sunset Dimming control DMX or DALI XI		
	Total harmonic distortion THD		9.8% max		
	Approvals		UL / CE / CCC / AS:NZS / EMC		
Physical	Dimensions		90mm x 90mm		
	Endplates		Screwed End Plates (Standard) / Screw-Less End Plates (Optional)		
	Weight per metre		3.21kg (7lbs) average weight		
	Housing		Aluminium Extrusion with standard silver powder-coat, black or white textured, (or) optional selected powder-coated finish		
	Baffle		Low glare black baffle as standard – optional body coloured baffle		
	Downward diffuser		Frosted acrylic lens		
	Connections		Polarised electrical connection between sections		
	Compatible ceiling type		Suitable for drywall ceilings, metal pan, concrete, timber and T bar grid ceilings		
	Mounting		Field adjustable rollerball wire suspensions / rod suspensions / wall mounting /surface mount		
	Joiner options		Lit corner 90° / Cross 90° / Tee 90° / Straight 180° join		
	Operating temperatures		Proformax = -25°C to 35°C (-13°F to 95°F)		
	Environment		Dry indoor applications only		
	Minimum length adjustment		Proformax = 50mm		
	LED board types		Proformax LED boards in 50 / 280mm / 560mm lengths Zhaga compatible		

STANDARD QUALITY ASSURED 7 YEAR WARRANTY

Xero Linear Lighting Systems
14 Voyager Circuit, Glendenning NSW Australia 2761

General Enquiries
P: +61 2 8599 9788
E: headoffice@xerolighting.com

XERO Linear Lighting Systems

XERO TECHNOLOGY SPECIFICATION XTS

XTS | 3.5 LD Square (Linear Darklighter)

Bend Options



135° | cross 90° | Tee 90° | custom | corner 90°

Optical Control



Plexiglass



Accessories and options



emergency packs

Rollerball Suspension

The smart suspension system that can be mounted on any surface whether a flat or sloped ceiling or even a wall

Axis geartray

This truly unique innovation adopts our revolutionary cam lock for quick and simple 'single person' installation. The system is also 'future proofed' by having the ability to easily upgrade as LED technology rapidly advances.



STANDARD QUALITY ASSURED 7 YEAR WARRANTY

Xero Linear Lighting Systems
14 Voyager Circuit, Glendenning NSW Australia 2761

General Enquiries
P: +61 2 8599 9788
E: headoffice@xerolighting.com

XERO Linear Lighting Systems