



XTA | 3.0 SLOT (PROJECT ONLY PRODUCT)



metric	80mm Wide x 115mm High
imperial	3.15" Wide x 4.52" High

THIS IS A PROJECT PRODUCT

Thank you for considering this project product. Please note that this product may require a longer lead time and a minimum order quantity. For more detailed information on this profile, we recommend speaking with your local Xero Specification Consultant. Visit xerolighting.com/contact for further assistance.



DATA TABLE




XTA | 3.0 Slot

LED Engine	4ft Length 1120mm	Luminous Flux (Delivered Lumens)	LO 1900	HO 3500	
	Xeramix	CRI	80+		
	Lumen Maintenance:	114,000 Hours (L90 B10 @ 50°)			
Proformax	CRI:	90+			
Proformax S	Lumen Maintenance:	82,000 Hours (L80 B10 @ 35°)			
Warranty	Xeramix		10 years		
	Proformax / Proformax S		7 years		
Electrical	Power Consumption		Between 20 and 45w/m		
	Voltage input range		120 – 277V		
	Control methods		Dimming options for white light: 0-10V, DALI, DMX Optional RGB / Sunset Dimming control DMX or DALI XI		
	Total harmonic distortion THD		9.8% max		
	Approvals		UL / CE / CCC / AS:NZS / EMC		
Physical	Dimensions		80 X 115 mm		
	Weight per metre		3.8kg (8.4lbs) average weight		
	Distribution		Symmetric		
	Housing		Aluminium Extrusion with standard silver powder-coat, black or white textured, (or) optional selected powder-coated finish		
	Diffuser		Frosted acrylic lens / Polycarbonate lens / microprism lens / Low UGR Plexiglass / Louvres available in White, Black, or Silver * Linear OPTIK series: includes 40° Beam, 60° Beam, 70° Beam, 90° Beam, 110° Wide Beam, 145° Extra Wide Beam, 165° Extra Wide Beam, Asymmetric Beam, Double Asymmetric Beam * NOTE: NOT AVAILABLE IN IP55		
	Connections		Speed connect joining system with polarised electrical connection between sections		
	Compatible ceiling type		Suitable for gyrock (drywall) ceilings, metal pan, concrete, timber and T-bar grid ceilings		
	Mounting		Field adjustable rollerball wire suspensions / rod suspensions / wall mounting / surface mount		
	Joiner options		Lit corner 90°/ Cross 90°/ Tee 90°/ Straight 180° Join		
	Operating temperatures		Xeramix = -25°C to 50°C (-13°F to 140°F) Proformax = -25°C to 35°C (-13°F to 95°F) Proformax S = -25°C to 35°C (-13°F to 95°F)		
	Environment		Dry indoor applications only		
	Minimum length adjustment		Xeramix = 1mm, Proformax = 25mm, Proformax S = 140mm		
	LED Board types		Xeramix LED boards in 25mm / 100mm / 280mm / 560mm lengths Zhaga compatible Proformax LED boards in 50mm / 280mm / 560mm lengths Zhaga compatible Proformax S LED boards in 140mm / 280mm / 560mm lengths Zhaga compatible		

Optical control

All XTA profiles come with many diffuser options for glare control in any application



*Linear OPTIK



Low UGR
plexiglass



Polycarbonate



Plexiglass



Microprism



Optic white
louvre




Louvre
powdercoated
White / Black / Silver

LINEAR OPTIK | *Beam angles

Asymmetric Double Asymmetric 40° Beam 60° Beam 70° Beam 90° Beam 110° Wide Beam 145° Wide Beam 165° Wide Beam

Accessories and options




XM3 Canopy
Kit



sensors / daylight
harvesting



emergency packs



downlights