



XERO
TECHNOLOGY
ADVANCED



XTA | 2.0 Edge Square

metric

60mm Wide x 77mm High

imperial

2.362" Wide x 3.0315" High

LINEAR
OPTIK 
OPTION


LOW UGR
OPTION

ADVANCED
INDUSTRY BEST
10 YEAR
WARRANTY

DATA TABLE

LED Engine	4ft Length 1120mm	Luminous Flux (Delivered Lumens)	LO 1900	HO 3500	
	Xeramix	CRI	80+		
	Lumen Maintenance:	114,000 Hours (L90 B10 @ 50°)			
Proformax	CRI:	90+			
Proformax S	Lumen Maintenance:	82,000 Hours (L80 B10 @ 35°)			
Warranty	Xeramix	10 years			
	Proformax / Proformax S	7 years			
Electrical	Power Consumption	Between 20 and 45w/m			
	Voltage input range	120 – 277V			
	Control methods	Dimming options for white light: 0-10V, DALI, DMX Optional RGB / Sunset Dimming control DMX or DALI XI			
	Total harmonic distortion THD	9.8% max			
	Approvals	UL / CE / CCC / AS:NZS / EMC			
Physical	Dimensions	60 X 77 mm			
	Weight per metre	3kg (6.6lbs) average weight			
	Housing	Aluminium Extrusion with: Standard – silver powder-coat, black or white textured, (or) optional selected powder-coated finish			
	Diffuser	Frosted acrylic lens / Polycarbonate lens / Microprism lens / Low UGR Plexiglass / Louvres available in White, Black, or Silver * Linear OPTIK series: includes 40° Beam, 60° Beam, 70° Beam, 90° Beam, 110° Wide Beam, 145° Extra Wide Beam, 165° Extra Wide Beam, Asymmetric Beam, Double Asymmetric Beam * NOTE: NOT AVAILABLE IN IP55			
	Connections	Speed connect joining system with the polarised electrical connection between sections			
	Compatible ceiling type	Suitable for gyprock (drywall) ceilings, metal pan, concrete, timber and T-bar grid ceilings			
	Mounting	Field adjustable rollerball wire suspensions / rod suspensions / wall mounting / surface mount			
	Joiner options	Lit corner 90° Cross 90° Tee 90° straight 180° join			
	Operating temperatures	Xeramix = -25°C to 50°C (-13°F to 140°F) Proformax = -25°C to 35°C (-13°F to 95°F) Proformax S = -25°C to 35°C (-13°F to 95°F)			
	Environment	(IP20) – Dry indoor applications only (IP55) Not in direct sunlight			
	Minimum length adjustment	Xeramix = 1mm, Proformax = 25mm, Proformax S = 140mm			
	LED Board types	Xeramix LED boards in 25mm / 100mm / 280mm / 560mm lengths Zhaga compatible Proformax LED boards in 50mm / 280mm / 560mm lengths Zhaga compatible Proformax S LED boards in 140mm / 280mm / 560mm lengths Zhaga compatible			

XTA | 2.0 EDGE Square
indoor series IP20

Optical control

All XTA profiles come with many diffuser options for glare control in any application



*Linear OPTIK



Low UGR
Plexiglass



Polycarbonate



Plexiglass



Microprism



Silver Louvre



Black Louvre



White Louvre

LINEAR
OPTIK

*Beam angles



Asymmetric



Double
Asymmetric



40° Beam



60° Beam



70° Beam



90° Beam



110° Wide
Beam




145° Wide
Beam



165° Wide
Beam

Accessories and options



XM3 Canopy
Kit



sensors / daylight
harvesting



emergency packs



downlights