

XERO  
TECHNOLOGY  
ADVANCED 

## XTA | 2.0 Slot

metric

60mm Wide x 91mm High

imperial

2.36" Wide x 3.58" High

LINEAR  
OPTIK   
OPTION

  
LOW UGR  
OPTION


ADVANCED  
INDUSTRY BEST  
10 YEAR  
WARRANTY

# DATA TABLE

LED Engine	4ft Length 1120mm	Luminous Flux (Delivered Lumens)	LO 1900	HO 3500	
	Xeramix	CRI	80+		
	Lumen Maintenance:	114,000 Hours ( L90 B10 @ 50° )			
Proformax	CRI:	90+			
Proformax S	Lumen Maintenance:	82,000 Hours ( L80 B10 @ 35° )			
Warranty	Xeramix		10 years		
	Proformax / Proformax S		7 years		
Electrical	Power Consumption		Between 20 and 45w/m		
	Voltage input range		120 – 277V		
	Control methods		Dimming options for white light: 0-10V, DALI, DMX Optional RGB / Sunset Dimming control DMX or DALI XI		
	Total harmonic distortion THD		9.8% max		
	Approvals		UL / CE / CCC / AS:NZS / EMC		
Physical	Dimensions		60 X 91 mm		
	Weight per metre		3.5kg (7.7lbs) average weight		
	Housing		Aluminium Extrusion with: Standard – silver powder-coat, black or white textured, (or) optional selected powder-coated finish		
	Diffuser		Frosted acrylic lens / Polycarbonate lens / Microprism lens / Low UGR Plexiglass Louvres available in White, Black, or Silver * Linear OPTIK series: includes 40° Beam, 60° Beam, 70° Beam, 90° Beam, 110° Wide Beam, 145° Extra Wide Beam, 165° Extra Wide Beam, Asymmetric Beam, Double Asymmetric Beam * NOTE: NOT AVAILABLE IN IP55		
	Connections		Speed connect joining system with polarised electrical connection between sections		
	Compatible ceiling type		Suitable for gyprock (drywall) ceilings, metal pan, concrete, timber and T-bar grid ceilings		
	Mounting		Field adjustable rollerball wire suspensions / rod suspensions / wall mounting / surface mount		
	Joiner options		Lit corner 90% / Cross 90% / Tee 90% / straight 180° join		
	Operating temperatures		Xeramix = -25°C to 50°C (-13°F to 140°F) Proformax = -25°C to 35°C (-13°F to 95°F) Proformax S = -25°C to 35°C (-13°F to 95°F)		
	Environment		(IP20) – Dry indoor applications only   (IP55) Not in direct sunlight		
	Minimum length adjustment		Xeramix = 1mm, Proformax = 25mm, Proformax S = 140mm		
	LED Board types		Xeramix LED boards in 25mm / 100mm / 280mm / 560mm lengths Zhaga compatible Proformax LED boards in 50mm / 280mm / 560mm lengths Zhaga compatible Proformax S LED boards in 140mm / 280mm / 560mm lengths Zhaga compatible		

## Optical control


All XTA profiles come with many diffuser options for glare control in any application



\*Linear OPTIK



Low UGR  
Plexiglass



Polycarbonate



Plexiglass



Microprism



Silver Louvre



Black Louvre



White Louvre

LINEAR  
OPTIK

\*Beam angles



Asymmetric



Double  
Asymmetric



40° Beam



60° Beam



70° Beam



90° Beam



110° Wide  
Beam




145° Wide  
Beam



165° Wide  
Beam


## Accessories and options




XM3 Canopy  
Kit



sensors / daylight  
harvesting



emergency packs



downlights