



XTA | 2.5 Loop SLOT

Metric: 71 x 100mm
Imperial: 2.795" x 3.937"

Wire or Rod Suspended
Surface Mounted
Removable Diffusers
Light Leak free
endplates
and joins

AVAILABLE
WITH
OPTIONAL

MULTI-BEAM
OPTIK 
optical control downlights



Data Table

Optic Module LED Engine	4ft Length 1120mm	Luminous Flux (Delivered Lumens)	LO 1900	HO 3500	
	Xeramix	CRI	80+		
		Lumen Maintenance:	114,000 Hours (L90 B10 @ 50°)		
	Proformax Proformax S	CRI	90+		
		Lumen Maintenance:	82,000 Hours (L80 B10 @ 35°)		
	24V RGBW System		Dual Row (DALI / DMX Dimming)		
Warranty	Xeramix		10 years		
	Proformax / Proformax S		7 years		
	24V RGBW		3 years		
Electrical	Power Consumption		Between 20 and 45w/m		
	Voltage input range		120 – 277V		
	Controls		0-10 volts / Dali Control Gear / DSI compatible / DMX / Dimmer switch / Constant light output / Motion sensor / Ripple free / Bluetooth mesh / Casambi control wireless system / Dimming options for RGBW; DALI, DMX		
	Total harmonic distortion THD		9.8% max		
	Approvals		UL / CE / CCC / AS:NZS / EMC		
Physical	Dimensions		71 X 100mm		
	Weight per metre		4.0kg (8.8lbs) average weight		
	Housing		Aluminium Extrusion with: Standard – silver powder-coat, black or white textured, (or) optional selected powder-coated finish		
	Diffuser		Frosted acrylic lens / Polycarbonate lens / Multi-Beam OPTIK Downlight available in 10° / 18° Spot Beams, 30° Medium Beam, 40° / 50° / 60° Wide Beams		
	Accessories		Various connection shapes available		
	Connections		Speed connect joining system with polarised electrical connection between sections		
	Compatible ceiling type		Suitable for gyprock (drywall) ceilings, metal pan, concrete, timber and T-bar grid ceilings		
	Mounting		Field adjustable rollerball wire suspensions / rod suspensions / wall mounting / surface mount		
	Bend Radii		430R / 830R / 1230R as standard with custom radii available (No unlit)		
	Joiner options		Lit corner 90° / Cross 90° / Tee 90° straight 180° join		
	Endplate Options		Conseal flat or optional curved end plates		
	Operating temperatures		Xeramix = -25°C to 50°C (-13°F to 140°F) 24V RGBW – (20°C to 35°C) Proformax = -25°C to 35°C (-13°F to 95°F) Proformax S = -25°C to 35°C (-13°F to 95°F)		
	Environment		(IP20) – Dry indoor applications only (IP55) – Not in direct sunlight		
	Minimum length adjustment		Xeramix = 1mm, Proformax = 25mm, Proformax S = 140mm		
	LED Board types		Xeramix LED boards in 25mm / 100mm / 280mm / 560mm lengths Zhaga compatible Proformax LED boards in 50mm / 280mm / 560mm lengths Zhaga compatible Proformax S LED boards in 140mm / 280mm / 560mm lengths Zhaga compatible		
	Configurations		Down only		


XTA | 2.5 LOOP Slot indoor series IP20

Optical control

All XTA profiles come with many diffuser options for glare control in any application




*Multi-Beam
Downlight




Polycarbonate
(Straights only)




Plexiglass



Accessories and Options



Loop Templates




XM3 Canopy
Kit



sensors / daylight
harvesting




emergency packs




downlights

XTA 2.5 LOOP SLOT


Standard Bend Options



1230R



830R




430R

*Other custom radii available on request


All radii bends can have integral drivers provided they adjoin a straight section
or are $\geq 1230R$

XTA|2.5LoopSLOT


Standard Arc Options




Minimum 30° segment
then each segment can be
increased in 7.5° increments
Arc segments below
1230R have remote drivers



430R






830R






1230R

Other options available on request

XTA 2.5 LoopSlot Standard Connections



Y Bends



V Bends

Other options available on request

Conseal is a patented end plate that is complete with 'magnetic snap' cover plate that's nothing short of impressive

50mm or 7.50° = the industry's smallest arc adjustment

Axis removable gear-tray for quick and simple 'single person' installation

The **NEW Conseal curved endplate** with 'magnetic snap' now offers you the choice to suit your next custom project

First of it's kind light leak free system

There are no light leaks in the usual places like end plates, diffuser expansion gaps and at joins where two or more pieces are connected together. The patented Lumi SEAL™ light leak free system incorporates - the SpeedConnect joining system and the Conseal end plate ensuring no light leaks.

'Speed-Connect' a fast easy to assemble tool-less joining system that minimises installation time and additional skilled labour and creates a light-leak free join.


Removable Diffuser with magnetic retention location locks

Soft Wiring with polarised plugs for easy interconnection of segments making loop the easiest curved profile on the market to install

XTA 2.5Loop SLOT

Rollerball Suspension


The smart suspension system that can be mounted on any surface whether a flat or sloped ceiling, or even a wall



XTA | 2.5 LOOP SLOT

Some examples of Shapes and Sizes

The LOOP series has the ability to form myriad of shapes and sizes from simple curved corners to the most complex configuration only limited by your imagination



NOTE: All of the above examples have been designed using standard radii

XTA | 2.5L∞pSLOT

Install Template

Xero Loop profiles come with the mounting templates that allow for easy installation.

The template should be assembled on the floor and the position in the room checked against the reflected ceiling plan then suspension positions should be laser transferred to the ceiling for accurate positioning before installing. Individual sections 'click' together to create an exact template of the actual luminaire.

Ease of installation is just another standard from the leader in linear lighting innovation.



Shape illustrated is an example only.
Templates are supplied for all individual designs and shapes